

PROPORTIONAL VALVES

Product Index

B



Function	Δ P		Temperature			Pipe connections	Series	Page	
	min. (bar)	max. (bar)	min. (°C)	max. (°C)					
SYNTHETIC BODY									
2/2 NC-NO	0	8	0	+60	Piezotronic (CNOMO, size 15)	pad mount (M5/1/8/instant fittings)	630	V104	
BRASS BODY									
2/2 NC	0	12	0	+60	Posiflow	M5, pad mount	202	V105	
2/2 NC	0	8	0	+50	Posiflow	1/8	202	V110	
2/2 NC	0	16	-10	+90	Posiflow	1/4 - 3/8	202	V115	
2/2 NC	0,3	10	-10	+90	Posiflow	3/8 - 1/2	203	V125	
2/2	0	10	-5	+90	MotorFlow ^D	3/4	610	V180	
BRONZE BODY									
2/2 NC	0	16	-10	+95	Compact ⁽¹⁾	1/2..1	E290	V162	
2/2 NC	0	16	-10	+184 ⁽¹⁾		1/2..2 1/2	E290	V162	
2/2 NC	0	16	-10	+184	Flanged ⁽¹⁾	DN 25..50	T290	V162	
3/2 NC	0	16	-10	+184	Flanged ⁽¹⁾	1/2..2	E390	V162	
STAINLESS STEEL BODY									
2/2 NC	0	8	0	+50	Posiflow	1/8	202	V110	
2/2 NC	0	16	-10	+90	Posiflow	1/4 - 3/8	202	V115	
2/2 NC	0	16	-10	+184 ⁽¹⁾		1/2..2 1/2	E290	V162	
2/2 NC	0	16	-10	+184	Clamp / Butt welding ⁽¹⁾	DN 15..65	S290	V162	
ALUMINIUM BODY									
2/2	0	8	0	+50	Flowtronic ^D , proportional valves	1/4	607	V154	
ACCESSORIES									
Electronic proportional control unit for Posiflow solenoid valves								908	V150
Controller module for Posiflow proportional valves								603	V152

⁽¹⁾ With: Positioner^D

(Potentially explosive atmospheres, see page 2)

