

AIR OPERATED POPPET VALVES AND SPOOL VALVES

Product Index



D

standards	ports/positions	function	pipe connections									max. pressure (bar)	flow at 6 bar l/min (ANR)	type	illustration	series	page	
			◯ - Namur mounting pad ▧ - instant fittings O.D. (mm) ◻ - internal thread ØG ⊥ - pad mount	6	1/8	1/4	3/8	1/2	3/4	1	1 1/4							1 1/2
VDMA/ISO15407-1 ISO 5599-1		NC NO																
Poppet valves																		
	3/2	● ●			◻ ◻							⊥	12	700-1750	DM		261 262	P415
	3/2	● ●				◻ ◻	◻ ◻	◻ ◻	◻ ◻	◻ ◻			12/16	4500-35000	DH		284 285 286	P420
	3/2	●												3000-31500	DP		266 267 268	P425
	4/2											⊥	16	2940-31500				P440
	4/2			▧	◻ ◻								10	210-840			263 264	P430
	4/2				◻ ◻							⊥	12	700-1750	DM		261 262	P435

standards	ports/positions	function	pipe connections										pad mount	max. pressure (bar)	flow at 6 bar l/min (ANR)	type	illustration	series	page	
			6	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	ØG								
VDMA/ISO15407-1 ISO 5599-1		NC NO																		
Spool valves																				
	3/2	●												10	860 3000 3800			551 552 553	P410-1	
	5/2																			P460-1
	3/2	●												8	400 175-1050			519 520 521	P450	
	5/2																			
	5/3														600-1050					
	5/2 5/3														600-900 550	Mega		578	P458	
	5/2														280				540 Ø4	P465
VDMA - ISO	5/2 5/3												8	500	ISO 02			538	P468-3	
	2x3/2 5/2 5/3												10	1150	ISO 01			539	P468-1	
ISO	5/2 5/3												10/12	1400 2800 4200	ISO 1 ISO 2 ISO 3			541 542 543	P470-1	
	5/2 5/3												12	6300-7000	ISO 4			544	P471-1	

00379GB-2006/R01
ASCO/JOUCOMATIC reserves the right to alter the availability, design and specifications without notice.