

AIR OPERATED POPPET VALVES AND SPOOL VALVES

Product Index



D

standards	ports/positions	function	pipe connections										max. pressure (bar)	flow at 6 bar l/min (ANR)	type	illustration	series	page		
			- Namur mounting pad - instant fittings O.D. (mm) - internal thread ØG - pad mount		ØG		pad mount													
VDMA/ISO15407-1 ISO 5599-1	NC NO																			
ISO	3/2	● ●												12	700-1750	DM		261 262	P415	
		● ●												12/16	4500-35000	DH		284 285 286	P420	
		●												16	3000-31500	DP		266 267 268	P425	
		●												10	5675	ISO 3		G34	P430	
														16	2940-31500	DP		266 267 268	P440	
	4/2														10	210-840			263 264	P433
														12	700-1750	DM		261 262	P435	

00379GB-2011/R01 Availability, design and specifications are subject to change without notice. All rights reserved.

standards	ports/positions	function	pipe connections									pad mount	max. pressure (bar)	flow at 6 bar l/min (ANR)	type	illustration	series	page	
			6	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2								ØG
VDMA/ISO15407-1 ISO 5599-1		NC NO																	
Spool valves																			
	3/2	●												10	860 3000 3800			551 552 553	P410-1 P460-1
	5/2																		
	3/2	●													400			519 520 521	P450
	5/2													8	175-1050				
	5/3														600-1050				
	5/2 5/3													10	1000-1700			L1 L2	P455-1
	5/2														280			540 Ø4	P465
	5/2 5/3														500	ISO 02		538	P468-1
VDMA - ISO	2x3/2 5/2 5/3														1150	ISO 01		CL18	P468-3
	5/2 5/3														1150	ISO 01		539	P466-1
	5/2 5/3														1150	ISO 01		CL26	P466-3
ISO	5/2 5/3													10/12	1400 2800 4200	ISO 1 ISO 2 ISO 3		541 542 543	P470-1
ISO	5/2 5/3													12	6300-7000	ISO 4		544	P471-1
ISO	5/2 5/3													10	1400 2800 4200	ISO 1 ISO 2 ISO 3		E12 E23 E34	P472-1